

Product datasheet

Specifications



Enclosure for modular device, Mureva Enclosure, 4x18 modules, earth and neutral terminal blocks

13437

 **Discontinued on:** 14 Mar 2022

 **Discontinued**

Main

Range	Mureva
Product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
enclosure type	Enclosure for modular device
Mounting plate description	Without mounting plate

Complementary

Enclosure mounting	Surface
9 mm pitches	36
Number of 18 mm modules per row	18
Total number of 18 mm modules	72
Number of horizontal rows	4
Electrical insulation class	Class II Double insulation
Provided equipment	4 marking kit 4 wiring strap 2 terminal block support 4 terminal block 32 holes
Type of front cover	Reversible Transparent
Power dissipation in W	89 W
[In] rated current	160 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	4 earth / neutral (screw connection) with 32 outgoers
Distribution block outgoers	64 x 10 mm ² 64 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	448 mm
Height	842 mm
Depth	160 mm
Internal depth	88 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Colour	Door: transparent green Enclosure: light grey (RAL 7035)
--------	---

Environment

Standards	IEC 60670-1 IEC 60670-24 EN 50262 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.000 cm
Package 1 Width	47.000 cm
Package 1 Length	85.000 cm
Package 1 Weight	8.010 kg
Unit Type of Package 2	P12
Number of Units in Package 2	11
Package 2 Height	80.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	100.110 kg

Logistical informations

Country of origin	IT
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	46 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	38 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.5 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	7 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	24 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5305d5d6-3783-4b3d-abd0-61fa4a6023d7
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
OECD PFAS Regulation	No OECD PFAS Chemicals Present
POP Directive	No POPs
Halogen-free status	Halogen free plastic parts product
PVC free	Yes

Use Again



Repack and remanufacture

Recyclability potential, in %	86
End of life manual availability	No need of specific recycling operations
Take-back	No