

Specifications



Eaton 285735

Eaton Z-SCH Installation contactor,
230VAC/50Hz, 4 N/C, 63A, 3HP

General specifications

PRODUCT NAME	Eaton Z-SCH contactor
CATALOG NUMBER	285735
MODEL CODE	Z-SCH230/63-04
EAN	4015082857356
PRODUCT LENGTH/DEPTH	82 mm
PRODUCT HEIGHT	72 mm
PRODUCT WIDTH	17.8 mm
PRODUCT WEIGHT	0.35 kg
COMPLIANCES	RoHS conform

Additional information

FEATURES

Additional equipment possible

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MIN -40 °C

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT 28 W

HEAT DISSIPATION CAPACITY 0 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT 0 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 63 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT 0 W

Technical data - mechanical

BUILT-IN DEPTH 60 mm

DEGREE OF PROTECTION IP40

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS) 4

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS) 0

NUMBER OF MODULAR SPACINGS 3

UTILITY CATEGORY 1

UTILIZATION CATEGORY (ACCORDING TO EN IEC 60947-4-1) AC-1

Delivery programme

AMPERAGE RATING 63 A

Technical data - electrical

INCANDESCENT LAMP LOAD - MAX 7740 W

LOAD FLUORESCENT LAMP - MAX 4060 VA

LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX 8120 VA

LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX 2668 VA

RATED OPERATING VOLTAGE (UE) - MAX 440 V

RATED OPERATING VOLTAGE (UE) - MIN 440 V

VOLTAGE RATING (EXCITATION) - MAX 253 V

VOLTAGE RATING (EXCITATION) - MIN 195.5 V

VOLTAGE TYPE AC

Resources

CATALOGUES [eaton-xpole-accessories-ca019015en-en-us.pdf](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/eaton-xpole-accessories-ca019015en-en-us.pdf)

DECLARATIONS OF CONFORMITY [eaton-contactors-declaration-of-conformity-eu250188en.pdf](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/eaton-contactors-declaration-of-conformity-eu250188en.pdf)

[eaton-wiring-diagram-z-sch-klem-bez4.jpg](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/eaton-wiring-diagram-z-sch-klem-bez4.jpg)

[eaton-3d-drawing-z-r-sch-einbau.jpg](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/eaton-3d-drawing-z-r-sch-einbau.jpg)

DRAWINGS [eaton-3d-drawing-sch-pack.jpg](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/eaton-3d-drawing-sch-pack.jpg)

[eaton-installation-contactors-3d-drawing-z-r-sch-einbau.jpg](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/eaton-installation-contactors-3d-drawing-z-r-sch-einbau.jpg)

[eaton-dimensions-ma-sch40.jpg](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/eaton-dimensions-ma-sch40.jpg)

INSTALLATION VIDEOS [Eaton Z-SCH and CMUC DIN-rail installation contactors unboxing](https://www.eaton.com/content/dam/eaton/products/switchgear-and-disconnectors/z-sch-klem-bez4/Eaton_Z-SCH_and_CMUC_DIN-rail_installation_contactors_unboxing)

MCAD MODEL	eaton-installation-contactor-mcad-3d-models-r40-r63-3mu.stp
	eaton-installation-contactor-mcad-drawings-r40-r63-3mu.dwg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

