

Luminaires | Floodlights

Aurora IP65 Proxima™
100W 13,000lm 4000K
Floodlight

EN-FLP100/40



Photometrics

Wattage	100
Lumens	13000
Lm/W	130
Beam Angle	100
Colour Temperature	4000
Ra	80
SDCM	5
UGR19	No

Product Features

Brand	Aurora
IP Rating	IP65
IK Rating	IK08
L80 Hours	50,000
Lifetime Class	L80
SKU Type	Non Dim
Dimmable	No
0-10V Dimming?	No

DALI Dimming?	No
1-10V Dimming?	No
DALI-2 Dimming?	No
DMX Dimming?	No
DSI Dimming?	No
Warranty	5 Years
Onsite Warranty	3 Year
Country of Origin	CN
Barcode	5056100000000

Electrical Specification

Input Voltage (Min)	100
Input Voltage (Max)	277
Input Voltage Type	AC
Power Factor	0.9
Surge Protection (kV)	2
Protection Class	Class 1
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	650

Physical Attributes

Width (mm)	275
Height (mm)	300
Material	Aluminium
Optic Material	Tempered Glass
Finish Colour	Black

Features

Marketing Feature 1	Aluminium housing for excellent heat dissipation
Marketing Feature 2	Salt spray tested

Marketing Feature 3	IP65 rated
Marketing Feature 4	IK08 rated
Marketing Feature 5	Prewired with 800mm of cable
Marketing Feature 6	L80 50,000hrs
Marketing Feature 7	5 Year Warranty
Marketing Feature 8	3 year onsite warranty (registration required) *Terms and conditions apply