

### Luminaires | Floodlights

## Aurora IP65 Vela<sup>™</sup> 30W 3000lm 4000K PIR Floodlight

EN-FLV30P/40



### Photometrics

<b>Wattage</b>	30
<b>Lumens</b>	3000
<b>Lm/W</b>	100
<b>Beam Angle</b>	110
<b>Colour Temperature</b>	4000
<b>Ra</b>	80
<b>SDCM</b>	6
<b>UGR19</b>	No

### Product Features

<b>Brand</b>	Aurora
<b>IP Rating</b>	IP65
<b>IK Rating</b>	IK06
<b>L70 Hours</b>	30000
<b>Lifetime Class</b>	L70
<b>SKU Type</b>	Non Dim
<b>Dimmable</b>	No
<b>0-10V Dimming?</b>	No

<b>DALI Dimming?</b>	No
<b>1-10V Dimming?</b>	No
<b>DALI-2 Dimming?</b>	No
<b>DMX Dimming?</b>	No
<b>DSI Dimming?</b>	No
<b>Warranty</b>	3 Years
<b>Barcode</b>	5056100000000

## Electrical Specification

<b>Input Voltage (Min)</b>	220
<b>Input Voltage (Max)</b>	240
<b>Input Voltage Type</b>	AC
<b>Power Factor</b>	0.9
<b>Surge Protection (kV)</b>	1.5
<b>Protection Class</b>	Class 1
<b>Frequency (Min) Hz.</b>	50
<b>Frequency (Max) Hz.</b>	60
<b>Operating Temp. (Min) °C</b>	-35
<b>Operating Temp. (Max) °C</b>	45

## Physical Attributes

<b>Width (mm)</b>	160
<b>Height (mm)</b>	118
<b>Material</b>	Aluminium
<b>Optic Material</b>	Tempered Frosted Glass
<b>Finish Colour</b>	Black

## Features

<b>Marketing Feature 1</b>	Aluminium housing for excellent heat dissipation
<b>Marketing Feature 2</b>	Tempered frosted glass
<b>Marketing Feature 3</b>	IP65 rated
<b>Marketing Feature 4</b>	IK06 rated
<b>Marketing Feature 5</b>	Pre-wired with 800mm of cable

**Marketing Feature 6**

Salt spray tested and approved

**Marketing Feature 7**

L70 30,000hrs

**Marketing Feature 8**

3 Year Warranty