

BEACON

Technical Specification



Product Code: UDTAKIT

Luckinslive 404179045

Description: Indication, Pull Cord and Reset Modules for Assistance Alarm Kit



Component 1 Description	Quantity	Component 2 Description	Quantity
UDTAPCM - Pull Cord Module	1	UDTAPLBM - Power, Light and Buzzer Module	1

General Information	
Dimensions (mm)	87 x 87 x 41
Colour	White
Pull Cord Length (m)	3 (Including 2 Triangular Bangles)
Plate Size	Single Gang
Materials	Anti-Microbial ABS
Mounting	Surface or Flush (Surface Box Included)
Anti-Ligature	Yes
Supply & Power	
Operating Voltage (V DC)	12
Maximum Cable Size (mm ²)	1.5
Power Consumption (W)	0.3
Environment	
Ingress Protection	IP20
Operating Temperature (°C)	-10 to +40

General Information	
Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Colour	White
Materials	Anti-Microbial ABS
Mounting	Surface or Flush (Surface Box Included)
Indication	LED illuminates in red when in alarm state
Activated Buzzer Sound Level (db)	>80
Purpose	Activation and Reset Circuits
Maximum Cable Size (mm ²)	1.5
Power Consumption (A)	0.2
Battery Backup	A23 Battery
Input Type	Ground & 2 live circuits - X1 & X2
Activation Type	Energise with a Normally Open Clean Contact
Output Type	1 Switched Live sharing common ground Separate output for additional sounders
Number of Outputs	2
Output Rating	12V 500mA
Ingress Protection	IP20
Operating Temperature (°C)	-10 to +40

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN

BEACON

Technical Specification



Product Code: UDTAKIT

Luckinslive 404179045

Description: Indication, Pull Cord and Reset Modules for Assistance Alarm Kit

Component 3 Description

UDTAREM - Assistance Alarm Reset Module

Quantity

1

General Information

Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Colour	White
Materials	Anti-Microbial ABS
Mounting	Surface or Flush (Surface Box Included)
Indication	LED illuminates in red when in alarm state
Buzzer Sound Level When Activated (db)	>80
Operating Voltage (V DC)	12
Maximum Cable Size (mm ²)	1.5
Power Consumption (W)	0.9
Ingress Protection	IP20
Operating Temperature (°C)	-10 to +40

Warranty Years 2

Features

Anti-Ligature Red Pull Cord

Accessories

UDTAPLBM: Assistance Alarm, Power, Light and Buzzer Module
UDTALBM: Assistance Alarm Light and Buzzer Module
UDTAPCM: Assistance Alarm Pull Cord Module
UDTASPC: Assistance Alarm Replacement Pull Cord
UDTAREM: Assistance Alarm Reset Module

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN