



VE212R

**Enclosure, vectorII, IP55, 24M**

**Technical properties**

**Connection**

Number of conduit inlets	12
--------------------------	----

**Voltage**

Nominal voltage	400 - 400 V
-----------------	-------------

**Installation, mounting**

Suitable for outdoor usage	No
----------------------------	----

Mounting on	Surface mounting
-------------	------------------

**Electric current**

Rated current	63 A
---------------	------

**Equipment**

Number of rails	2
-----------------	---

Number of rows	2
----------------	---

Number of section in width	1
----------------------------	---

With lock	No
-----------	----

Has neutral terminal block	Yes
----------------------------	-----

Has earthing terminal block	Yes
-----------------------------	-----

Has mounting plate	No
--------------------	----

**Capacity**

Number of modules	24
-------------------	----

**Functions**

With conduit inlets	Yes
---------------------	-----

**Dimensions**

Height	427 mm
--------	--------

Width	310 mm
-------	--------

Depth	151 mm
-------	--------

Number of width units	12
-----------------------	----

**Cover, door**

Number of cabinet doors	1
-------------------------	---

Number of locks	0
-----------------	---

Door/cover is transparent	Yes
---------------------------	-----

**Materials**

Material	Plastic
----------	---------

RAL code	7035
Colour	Light grey
Ultraviolet-resistant	No

---

**Safety**

Protection class	Isolation class II
Impact resistance IK	IK08
Ingress Protection (IP) class	IP65
Locking type	Snap on lock, Without lock
Glow wire test	750 °C