

Product	Emergency pack		
Code	WAREM		
Product Features	<ul style="list-style-type: none"> <li>• Safety isolation</li> </ul>	<ul style="list-style-type: none"> <li>• ( - 25°C ) Low temperature start</li> </ul>	
	<ul style="list-style-type: none"> <li>• High reliability and long life</li> </ul>		
INPUT	VOLTAGE RANGE	176 ~ 264Vac	
	NOMINAL INPUT VOLTAGE	220 ~ 240Vac	
	FREQUENCY RANGE	47 ~ 63HZ	
	EFFICIENCY(Typ.)	> 60% (240Vac full load)	
	AC CURRENT (MAX.)	< 0.1A	
	Standby Power(Typ.)	< 1.2W	
	RATED POWER	2W	
OUTPUT	Charging voltage	4-5V	
	Charging current	60mA-100mA	
	Discharge voltage	3V	
	Discharge current	400mA/3.2V	
	Battery	3.2V/1500mA	
	SETUP TIME	<500ms/230VAC@full load	
	SHORT CIRCUIT	Protection type: Hiccup Model	
	WITHSTAND VOLTAGE	Input - Output:3.0KVac 3S	
ENVIRONMENT	WORKING TEMP	-30 ~ +55°C	
	WORKING HUMIDITY	20 ~ 90%RH non-condensing	
	STORAGE TEMP,HUMIDITY	-40 ~ 80°C, 10 ~ 95%RH	
	VIBRATION	10 ~ 500Hz,5G 10min./1cycle,60min.each along X,Y,Z axes	
OTHERS	SAFETY STANDARD	EN60950-1	
	LIFE TIME	≥5.0 YEAR	
Product image			
			