

Specifications



Eaton SD-LTE

Eaton Speech dialler, Mobile networks,
Voice, SMS

General specifications

PRODUCT NAME	Eaton speech dialler
CATALOG NUMBER	SD-LTE
EAN	5060096858485
PRODUCT LENGTH/DEPTH	30 mm
PRODUCT HEIGHT	115 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	0.25 kg
COMPLIANCES	CE marking
CERTIFICATIONS	CE

More additional specifications

ATS RATING	Not applicable
CONTACTS	10
CURRENT - MAX	170 mA
CURRENT NORMAL	50 mA
EN 50131 GRADE	Not applicable
ENCLOSURE COLOUR	White
ENCLOSURE MATERIAL	Plastic
ENVIRONMENTAL CLASS	Class II
INTERNAL AERIAL	Not applicable
LISTEN IN	Yes
MAXIMUM NUMBER OF INPUTS	8
MESSAGES - SMS	8
MESSAGES - SPEECH	8
MOUNTING	Surface
NUMBER OF INPUTS - MAX	8
NUMBER OF RELAY OUTPUTS	Not applicable
NUMBER OF TRANSISTOR OUTPUTS	4
PROGRAMMING DISPLAY	LCD
RADIO FREQUENCY	850/900/1800/1900MHz
REMOTE ACCESS	Yes
SUPPLY	12 VDC
SUPPLY - MAX	28 VDC
SUPPLY - MIN	10.5 VDC
TALK BACK	Yes
TEMPERATURE SENSOR	Yes
TRANSISTOR OUTPUTS	4
TYPE OF COMMUNICATOR	Communicator
VDS CLASS	None
WIRED INPUT TYPE	CC
WITH HOUSING	Yes
WITH POWER ADAPTOR	No
OPERATING TEMPERATURE - MAX	55 °C
OPERATING TEMPERATURE - MIN	-10 °C
TYPE OF CURRENT	DC

Resources

BROCHURES [Scantronic security systems - Product range brochure](#)

CATALOGUES [SD1 and TSD2 Speech dalliers - Datasheet](#)
[SD3 and SD-GSM Speech dalliers - Datasheet](#)
[SD1 EC Speech dalliers - Declaration of conformity](#)
[SD GSM EC Speech dallier - Declaration of conformity](#)
[SD3 EC Speech dalliers - Declaration of conformity](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

